

Scara cu platforma,deplasabila, sudata, tip PSS



Executie ca scara conf. normei **EN 131-7** iar executia ca platforma conf. normei **EN 14122**

Sistemul SANT (trei procedee INDEPENDENTE de imbinare: bolt, nituire, sudura) duce, deasemeni, la triplarea rigiditatii si sigurantei in utilizare [vezi si VIDEO:](#)



incarcare maxima admisibila: **150kg**

lonjeroane si trepte din aliaj de **aluminu extrudat** (nu din tabla sudata)

deplasarea cu **2 roti** montate pe traversa de baza

OBS: **MPSS varianta sudata** difera fata de **MPSA varianta asamblabila** prin faptul ca **la varianta sudata Platforma, Traversa Spate, Rigidizarile si Scara** sunt **sudate intre ele**,

iar **Balustradele** se **monteaza la beneficiar**. Acest lucru face ca varianta sudata sa fie mai scumpa decat varianta asamblabila, deoarece are gabarit mai mare ceea ce implica cheltuieli de transport mai mari



Tip	Nr. trepte	H1 [mm]	H2 [mm]	H lucru [mm]	L [mm]	Masa [kg]	Inaltime max. de lucru [m]
PSS3	3	640	1640	2840	960	11	2.84
PSS4	4	850	1850	3050	1050	12.5	3.05
PSS5	5	1070	2070	3270	1140	14	3.27
PSS6	6	1280	2280	3480	1220	15.5	3.48
PSS7	7	1490	2490	3690	1310	17	3.69
PSS8	8	1700	2700	3900	1390	18.5	3.9

Caracteristici produs:



Caracteristici generale

- inaltime balustrade platforma: **1000 mm**
- latime tronsoane scara: **550 mm**
- dimensiuni lonjeroane: **61,4 x 23 mm**
- grosime pereti lonjeroane si trepte: **1,3 mm**
- latime trepte: **80 mm**
- distanta intre trepte: **230 mm**
- platforma de sus din **aluminu striat**
- aria platformei: **550 x 700 mm**
- **dopuri** de plastic **antiderapante** la baze
- **2 roti** de diametru **75 mm**
- balamale din otel zincat
- dopuri de plastic antiderapante la baze

